


# REVERSE OSMOSIS SYSTEM

System Part Number: EV9975-55



with optional wall mount

Leveraging proprietary technology, the system uses Reverse Osmosis (RO) to reduce Total Dissolved Solids (TDS); it provides up to 375 gal/day (1,419 L/day)\* and includes a two-gallon (7.6 L) hydropneumatic tank. Ideal for applications where RO is necessary to meet manufacturer's warranty requirements†.

Combi ovens

Steamers

Proofers

with optional wall mount



with optional wall mount

Meets combi oven and steamer equipment water quality standards; reduce scale and corrosion problems due to high TDS, water hardness\*, and chlorides†

4CM cartridge provides optimal mineral content for proper function of conductivity sensors on steam equipment

Non-electric design operates on available water pressure†

Sealed hydropneumatic storage tank provides capacity and pressurized water to downstream equipment

Compact design allows installation under counters and in tight spaces

Pressure gauge allows monitoring of RO

Built-in bypass, sample port and cartridge replacement

decrease product life. Also can reduce sediment and chlorine to help protect the RO membrane\*

line to equipment

Installation kit comes complete with for installation

to two times more water than standard RO membranes†

Numerous patents pending on technology and other aspects of the product design

Feed water connection to system—should be COLD only. Tempered water up to 80°F

For use with steam generation only. Do not use for condensate or wash water.

Provide a dedicated feed water supply

Detailed, illustrated installation guide is included with each system.



| China |