


Coffee

FEATURES • BENEFITS

Meets espresso, coffee, and tea standards; known to significantly reduce

Proprietary Fibredyne™ II filtration media effectively inhibits growth of bacteria on the filter media that can decrease product life. Also can reduce

floor stand bracket



High flow 1/2" OD tubing optimized water


tubing, fittings, and mounting hardware for installation

High efficiency RO membrane saves up

technology and other aspects of the

Pressure gauge allows monitoring of RO inlet pressure and prefilter condition

Flush valves speed up installation and



INSTALLATION TIPS

*Not performance tested or certified by NSF.

Allow 3" clearance below system for filter

(26.6°C) can be used.

Do not exceed system text exceed

RO systems with 25% recovery.
EPA Est. 002623-IL-003



United States | J a U | A' U | 9% | o; UZ% A ; E' | " | g' PE A U " | J % | s Y | o; U k a U | x | E a U s i C | i f i c Y | U s | x | E a U s i C
Australia | " | J f E % ' U | " | % c | E i E ± " f a a' p | " | " a Y a U % | " | d; A | % | o; U k a U | x | E a U s i C
China | " | 5 " A a c' Z A % % d K P | " | " % ± % | " | China | " | d; A | s' % % % U | x | E a U s i C
India | | f a A o % ! | " | a' 5 A f U d i o; U | ~ | s a U | " | K i % | " | d; A | % c % a Y a C | U | x | E a U s i C
Europe | | Z; E a U q % U | | A % C | p | ; E c a Y a U | x % A q | A Y a | d | | A i C Y a % | " | 9; U E a U | | | A % C | " | d; A | Y % Y | o; U k a U | a U | x | s i C
Japan | | C % % ; E s | " | 9 % | C f a J K | A ± | 5 | " | 9 % | C f a J U f i U A a ~ % % C | % % Y | " | D % % % % | " | C % % | " | d; A | % f | | o; U k a U | s i A
Southeast Asia | | " | 9 % | A s A | i % | " | " | D % ± Y " | E a U | " | % ± % d U | " | " | d; A | s Y | o; U k a U | x | A