


## SYSTEM DESCRIPTION

Leveraging proprietary technology, the **EZ-RO 650/16ATM** system uses Reverse Osmosis (RO) to reduce Total Dissolved Solids (TDS); it provides up to 650 gal/day (2,460 L/day)\* and includes a 16-gallon (60.6 L) atmospheric tank. Ideal for applications where RO is necessary to meet manufacturer's warranty requirements

# EZ-RO™ 650/16ATM REVERSE OSMOSIS SYSTEM

EV9975-70



## System

**Overall Dimensions - Processor**  
22.8" H x 17.4" W x 8.0" D  
(57.9 cm x 44.2 cm x 20.3 cm)

**Tank Dimensions & Capacity**  
22.3" H x 18.5" W x 25.6" D  
(56.6 cm x 47.0 cm x 65 cm)  
16 gallons (60.6 L)

**Connections**  
Inlet: 3/8" push-to-connect  
Outlet: 1/2" OD push-to-connect;  
3/4" garden hose connection  
included

**Pressure Requirements**  
50 - 100 psi  
(3.5 - 6.9 bar), non-shock

**Water Temperature**  
40-100°F (4 - 38°C)

## System

**Shipping Weight**  
74.0 lbs (33.6 kgs)

**Electrical Connection**  
Grounded 115 VAC, 2 Amp

## Performance

**Daily Production Rate**  
Up to 650 gpd (2,460 Lpd)\*  
nominal at 77°F (25°C), 750 ppm  
NaCl, 60 psi (4.1 bar) feed water  
pressure\*; production will  
vary based on water supply  
temperature and pressure

**Service Flow Rate**  
Dependent on water level up to  
3.25 gpm (12.3 L) @ 50 psi (3.4 bar)

16-gallon atmospheric tank



For Pentair Everpure Product Warranties visit:  
<http://pentair.com/assets/foodservice-warranty>

For Pentair Patent Information visit:  
<http://pentair.com/patents>

United States | Australia | Canada | China | India | Europe | Japan | Southeast Asia

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners.