



# CLEAN AND CLEAR® FILTER SYSTEMS



The Clean & Clear Filter System pairs the OptiFlo® Pump with the Clean & Clear Cartridge Filter, a quality filtration unit using a thermoplastic chemical-resistant tank. All models are equipped with easy access to the filter for maintenance and plumbing.

Ordering Information


# PLM SERIES FILTER SYSTEMS

The System:2 Mod Media PLM Series Aboveground System

**Dimensions and Performance**



# EASYCLEAN™ D.E. FILTER SYSTEMS

D.E. Filter System comes in a variety of sizes to suit most

## Ordering Information

Product	Pump THP	Pump Cord	Hose Kit

<sup>1</sup>

<sup>2</sup> Flow Rate and Turnover Capacity based on Filter.

<sup>3</sup> WARNING: A suitable ground fault interrupter (GFCI) should always be installed on aboveground system equipment.

## Dimensions and Performance

OptiFlo Pump



See page 353 for replacement parts.

# SAND DOLLAR® FILTER SYSTEMS




Sand Dollar Filter System<sup>2</sup>

Our blow-molded process creates a one piece, non-corrosive tank of outstanding strength

provides excellent performance.

## Featured Highlights

- Six-position 1-1/2 in. multiport valve
- New 1.0 THP OptiFlo® Pump
- One piece, durable non-corrosive tank
- Combination water and sand drain makes servicing and winterizing fast and easy
- Unionized Pump to Filter connection



## Ordering Information

Product	Pump THP	Pump Cord	Hose Kit (Ft.)	Effective Filtration Area (Sq. Ft.)	Flow <sup>1</sup> Rate (GPM)	Turnover Capacity (In Gallons) <sup>1</sup>			Tank Diameter (In.)	Tank Height (In.)	Sand Required (Lbs.)
						8 Hour	10 Hour	12 Hour			
<b>SAND DOLLAR FILTER SYSTEMS</b>											
PNSD0035OE1160	1.0	Standard plug 3 ft cord	6 ft	1.4	35	16,800	21,000	25,200	16	28-1/2	100
PNSD0035OE11X0	1.0	Standard plug 3 ft cord	None	1.4	35	16,800	21,000	25,200	19	34	150
PNSD0040OE1162	1.0	Standard plug 3 ft cord	6 ft	1.8	40	19,200	24,000	28,800	19	34	150
PNSD0040OE11X0	1.0	Standard plug 3 ft cord	None	1.8	40	19,200	24,000	28,800	19	34	150
PNSD0040OE1260	1.0	Twistlock plug 3 ft cord	6 ft	1.8	40	19,200	24,000	28,800	19	34	150
PNSD0060OE1160	1.0	Standard plug 3 ft cord	6 ft	2.3	60	28,800	36,000	43,200	22	35-1/2	250
PNSD0060OE11X0	1.0	Standard plug 3 ft cord	None	2.3	60	28,800	36,000	43,200	22	35-1/2	250
PNSD0060OE1260	1.0	Twistlock plug 3 ft cord	6 ft	2.3	60	28,800	36,000	43,200	22	35-1/2	250

<sup>1</sup> Flow Rate and Turnover Capacity based on Filter.

<sup>2</sup> WARNING: A suitable ground fault interrupter (GFCI) should always be installed on aboveground system equipment.

## Dimensions and Performance



See pages 355 for replacement parts.

## Featured Highlights

- for performance.
- One-piece polyethylene tank
- Multi-port valve selector activates backwashing action with one quick turn
- Easy-to-read top-mounted pressure gauge

installation and servicing

large capacity OptiFlo Series pump. Low maintenance







